

2X-LB

Addressable Fire Panel Accessory - Loop Expansion Board - 2 loop

Overview

The loop board with pluggable connectors adds 2 additional loops to your 2-loop low-end addressable fire panel that doubles the amount of devices to be supported by one panel and 128 extra zones can be programmed. Together with the 2 additional loops, 4 supervised sounder/fire-routing outputs, which can be used as freely programmable outputs, come along as well.

The Application

The loop board allows for bigger single panel applications. Instead of using two 2-loop panels you now have only one panel to power and all the loop wiring is concentrated to one location without having to use a Firenet network.

In case you need to expand an existing system you don't need to put another panel in place. You only have to add the loop board. This makes your system more flexible and easier to expand.

Please note that only the 2-loop panel has this capability of adding the additional loop board.

Mounting

The board can be plugged directly on the front of the main board of the panel on the easy to remove chassis. No additional cabling needs to be done.



Details

- 2 loops and adds up to 128 zones
- 4 programmable outputs
- Pluggable connectors
- Plugs directly on the front of the main board and chassis

2X-LB

Addressable Fire Panel Accessory - Loop Expansion Board - 2 loop

Technical specifications

Loop

Maximum Loop Capacity 2

Output

Programmable 4, 700mA / 19.5-28VDC (24VDC nominal)
(supervised)

Termination 15 kohm

Physical

Form factor Large

Physical dimensions 127 x 55 x 152 mm (W x H x D)

Net weight 120 g

Shipping weight 192 g

Mounting type Surface mount

Environmental

Operating temperature -8 to +42°C

Storage temperature -10 to +50°C

Relative humidity 95% max. noncondensing

Standards & regulation

Certification EN54-13, EN54-2, EN54-21, EN54-4

Standards EN54-2
EN54-4
EN54-13
EN54-21

Environmental CPD
WEEE
RoHS

Outputs

Cable type Recommended 2 core 1.5 mm² twisted pair

Loops

Outputs 2, 250 mA / 29VDC (29VDC to 36VDC)

Cable length 56ohm / 1µF max. 2 km

Cable type Recommended 2 core 1.5 mm² twisted pair

