

Manual callpoint, flush mount, red, 560 ohm and free contact, with break glass

DMN700R

The DMN700R is a red manual call point for flush mount applications. It has an internal 560 ohm series resistor and free contact. It is supplied with a break glass and test key. Surface mount applications require the addition of the DMN787.

Specifications

Cable Termination	0.5 - 2.5 mm ²
Max. contact rating (resistive load)	2A @ 30 VDC
Series resistor	560
Mechanical	
Material	PC/ABS
Weight	110g
Colour	Red
Environmental	
Operating temperature	-10°C to +55°C
Storage temperature	-10°C to +55°C
Relative humidity (non-condensing)	0-95%
IP Rating	IP24D

Ordering Information

DMN700R	Manual callpoint, flush mount, red, 560 ohm and free contact, break glass
DMN787	Surface mounting box with earth connector, red
DM711	EN54 universal glass ARITECH branded
DM715	EN54 Universal MCP Glass (without branding)
DMN782	Hinged transparent MCP protection cover
DMN784	Call Point Test Key
DMN798	Breakable Seal for DM2010, DMN700, DMN900 and KAL455 Series Manual Call Points
DMN800	Resettable Element for DM2010, DMN700, DMN900 and KAL450 Series MCPs



- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards