

AS372

Conventional Intrinsically Safe, Multi-Tone Electronic Sounders

General

The AS372 is electronic sounder suitable for all intrinsically safe signalling applications including fire, security and process control. It provides an audible warning signal in case of alarm.

Ratings

The AS372 is ATEX approved with and ExII 1G and EEx ia IIC T4 rating. It is housed in a flame retardant ABS housing with a UL94V0 & 5VA rating, and is ingress protected to IP65.

Efficient and versatile

The AS372 provide high sound output at low current, reducing power requirements and overall system cost.

With a choice of 49 different user selectable tones, the required tone can be selected during installation. A second and third tone is available for multi-phase evacuation applications. With volume control on board as standard, it allows for full flexibility for accomplishing exact audio output requirements for every installation.



Details

- ATEX approved
- EEx ia IIC T4 rating
- 49 Tones user selectable
- Automatic synchronisation
- Surface mount
- Volume control
- IP65

AS372

Conventional Intrinsically Safe, Multi-Tone Electronic Sounders

Technical specifications

Electrical

Operating voltage	16 to 28 VDC
Supply voltage (via barrier)	16 - 28 VDC
Nominal current (tone dependant)	25mA @ 24V

Physical

Physical dimensions	89 x 99 mm
Net weight	350 g
Colour	Red (RAL 3000)
Housing (flame retardant)	UL94V0 & 5VA FR ABS
Colour	Red (RAL3000)
Fixings	Stainless steel
Cable entry	2 x M20 clearance gland knockouts
Gland Rating (not supplied)	IP20 or better
Cable support	0.5 to 2.5mm ²
Dimensions (Ø x D)	89 x 99 mm
Weight	350g

Environmental

Operating temperature	-40 to +60°C
Storage temperature	-40 to +70°C
Relative humidity	95% noncondensing max.@20°C
Environment	Indoor, IS, Outdoor
IP rating	IP65
Ingress protection	IP65
Operating temperature	-40°C to +60°C
Storage temperature	-40° to +70°C
Relative humidity	<90% @ 20°C

Standards & regulation

Certification	CENELEC/ATEX
---------------	--------------

Performance

Sound output @ 1 m (tone dependant)	< 100dB(A) ± 3dB
Number of tones (UKOOA/PFEER compliant)	49
Number of stages	3
Effective range @ 1 kHz	40m
Operation	Continuous
Automatic synchronisation	Phased start
Line monitoring input	Polarised

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

