

# DM2080I-N 2000 Series Addressable MCP w/ Isolator - RED

#### General

The DM2080I-N is an addressable, 2000 series RED manual call point with dual isolator included. Its double action push button has a latching mechanism and is designed according to DIN14655 standards. It is supplied in a in a durable plastic housing with alarm indication LED and has a door opening angle of more than 180° for ease of access.

#### Installation

The DM2080 is made ready for installation on German junction boxes. The enclosure has an IP rating of DIN IP42 and boasts generous space for the wiring. A t-insulator separates the outside from the inside, and a connector for screened cable in the connection area is available. A yellow LED is available internally to indicate the status for the isolator.

#### Approval

The DM2080I-N is VdS approved: G 203056



#### **Details**

- Type B (double action) manual call point
- Includes dual isolator
- RED (alarm) and YELLOW (Isolated) LEDs Complies to DIN14655
- Door opening angle >180°
- Complies to DIN14655
- VdS Approved

## DM2080I-N 2000 Series Addressable MCP w/ Isolator - RED

### **Technical specifications**

General	
Status indication	LED
Compatibility	Aritech 2000 systems
Connectivity	2-wire loop
Addressing method	DIP Switches
Electrical	
Operating voltage	17 - 28 VDC
Current consumption	<1 mA (quiescent) < 4 mA (alarm)
Detection	
Detection principle	Microswitch
Monitoring	Device type, Presence
Coverage area	Defined by local installation rules
Isolation	
Туре	Negative line break
Series resistance	0.1 ohm (line resistance)
Physical	
Physical dimensions	125 x 125 x 36 mm (W x H x D)
Net weight	225 g
Colour	Red (RAL 3001)
Mounting type	Wall mount
Material (body)	RA6 + 30%gF
No. of cable cores	2
Functional marking	House on Fire
Environmental	
Vandal proof	No
Operating temperature	-10 to +50°C
Environment	Indoor
IP rating	IP42
Standards & regulation	
Compliancy	CE, REACH, RoHS 2, WEEE
Certification	CPR

EN54-11, EN54-17

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.



Standards