#### **Product data sheet**



## DM861-0

### MCP Yellow, Gas Manual Release, 100 Ohm, English, Dutch & French

#### General

The DM861-0 is a Type B / Dual action manual call point for surface mount applications. It is specifically designed for use with the FEC403EN gas extinguishing panel, and includes language inserts for English, Dutch & French.

#### Construction

The rugged aluminum housing, combined with a fade resistant coating guarantees a long lasting high quality product. The revolving door, with an opening angle of 180°, contains an interchangeable break glass. The revolving door also contains a special clip, which features as a failsafe, to prevent the door from being closed while the unit is still triggered.

#### **Dual action**

The DM861-0 is defined as a type B /dual action manual call point, due to the fact that two actions are required to trigger the manual call point. First the break glass must be broken, and secondly the button must be pushed.





#### **Details**

- EN12094-3 approved
- Robust aluminium housing
- Type B / Dual action
- Surface mount

# DM861-0

## MCP Yellow, Gas Manual Release, 100 Ohm, English, Dutch & French

### **Technical specifications**

Physical	
Physical dimensions	125 x 125 x 34 mm (W x H x D)
Net weight	400 g
Colour	Yellow
Environmental	
Operating temperature	-20 to +60°C
Environment	Indoor
IP rating	IP43
Standards & regulation	
Certification	EN12094-3
Series resistor	
	100 ohm
Housing	
	Aluminum
Dimensions	
	125 x 125 x 34 mm
Weight	
	400g
Color	
	Yellow
Operating Temperature	
	-20°C to +60°C
IP Rating	
	IP43

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

