

FE245

Door Holder, Wall Mount, 400N, with Release Button

General

The FE245 is a wall mount door holder, in a Bayblend housing, which offers a 400N holding force and a release button.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE245 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Keeper plate included

FE245

Door Holder, Wall Mount, 400N, with Release Button

Technical specifications

General

Holding force N (Newton) 400

Release button Yes

Spark suppression diode Yes

Reverse polarity protection Yes

Electrical

Power supply type 24 VDC

Power consumption 1.6 W

Duty cycle 100%

Physical

Physical dimensions 70 x 70 x 65 mm (H x W x D)

Environmental

IP rating IP54 (magnet)
IP42 (connection)

Standards & regulation

Standards EN1155

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 12 March 2020 - 16:22



**United
Technologies**

Climate | Controls | Security